



ECG-1106L

Digital Six-Channel ECG



Electrocardiograph

Features

- 5.6 inch color LCD touch screen, 12-lead simultaneously acquisition
- 180 ECG files can be saved in the ECG
- Over 5000 ECG files can be saved to SD card(optional)
more ECG files can be stored via USB port
- Freeze, Pre-10-second print and Trigger print function to observe any abnormal ECG waveforms
- HR detection alarm and pacemaker detection supported
- Cine-loop function: saved ECG waveform can be played back
- Auto-save function: users can choose whether to automatically save the files with the printout or not
- Support magnetic card reader, bar code scanner, make information input more conveniently
- Support external laser printer to achieve A4 size report output
- Data management software on PC(optional)
- Reliable automatic measurement & Interpretation tested with CSE&AHA database

ECG-1106L

Digital Six-Channel ECG



Basic Specification

Input Circuit:	Floating, protection against defibrillator and pacemaker detection
Lead:	Standard 12-lead
Input Impedance:	≥50MO
Input Circuit Current :	≤50nA
Leakage Current :	<10μA
Calibration Voltage:	1mV±2%
A/D Convertor:	24bits
Frequency Response:	0.05Hz~165Hz (-3dB)
Time Constant:	≥3.2s
Noise Level:	<12μVp-p
Filter:	AC: 50/60Hz (-20dB); EMG:25Hz/35Hz/45Hz(-3dB); ADS and Baseline auto-adjustment
Sensitivity:	AUTO, 2.5, 5, 10, 20, 40 (mm/mV ±5%)

Record Data

Measurement:	HR, PR/QT/QTC Interval, P/QRS/T Axis etc.
Patient Data:	Date, Time, ID, Name, Gender, Age, Height, Weight etc.
System Data:	Sensitivity, Speed, Institution etc.
Analysis Report:	On/Off selectable

Print System

Printer:	High speed and sensitivity thermal dot recording system
Speed:	5, 6.25, 10, 12.5, 25, 50(mm/s, ±3%)
Paper:	Roll paper112mm×20m(30m)

Power Source

AC :	100V-240V(±10%) , 50/60Hz(±1Hz)
DC :	More than 2-hour continuous operation time with lithium battery after fully charged

Input&Output

Safety Classification:	Type CF
Safety Standard:	MDD93/42/EEC,IEC60601-2-25, IEC60601-1,IEC60601-2-51:2003, ANSI/AAMI EC-11,EN 1441-1997

Input&Output

External Input:	10mm/V ± 5%; Input Impedance=100KO
ExternalOutput:	1.0V/mV± 5%; Output Impedance=100O

Size&Weight

EquipmentSize:	345 x 300 x 80mm
Carton Size:	400 x 180 x 355mm
Net Weight:	2.5Kg(battery included)
GrossWeight:	4.5Kg



USB



※ Specification subject to change without prior notice

Medguard Professional Healthcare

Tel: +353 (0) 1 835 2411

Email: sales@medguard.ie

Fax: 01 969 5009

Website: www.medguard.ie

Unit 6/7, Block 4, Ashbourne Business Park, Ashbourne, Co. Meath, A84 VK52

